

BPEO Fibre Closure BPEO-S2-CDP



Part Number:
B2-CDP-0000-000-000-0000

Fibre Closures BPEO are designed with flexibility in application in mind. Available in a range of sizes, they can be deployed above grade (pole, facade) or below grade (manhole, handhole). These closures can be used for fibre-to-the-home (FTTH) deployments and any type of optical fibre cable deployment in the outside plant. Mechanical and tool free: Easy to re-enter and close; integrated sealing gasket keeps water out. The built-in seals of the BPEO in conjunction with the latch mechanism ensure that the closure remains watertight even after frequent use. The sealing gasket requires no replacement and no addition of sealant material, even after several open/close operations.

Features and Benefits

Fibre organiser (ramp or flat)

Enables fibre and tube management, supports single fibre management

Tool-less opening and closing

Quick-and-easy installation

Use of ECAM: External Cable Assembly Module

Easy and fast addition of loop and drop cables, without disrupting already installed fibre and protecting the fibre organiser of any debris

Integrated sealing gasket

Ensures water tightness and remains functional even after several open/close operations

IP68 design

Reliable and watertight with an integrated valve for flash on-site testing

BPEO Fibre Closure BPEO-S2-CDP



Specifications

General Specifications

Application	Aerial / Manhole
Environment	Outdoor
Cable type	Round
Mounting Type	Anchoring
Product type	Splice Closure
Branching	Yes
Brand	BPEO

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Environmental Conditions

Temperature range, operation	-40 °C to 65 °C
------------------------------	-----------------

Design

Splitter support	Yes
Capacity (number of splices)	720
Closure shape	Dome
Closure type	Canister
Drop cable type	SST flat or round
Fibre Type	Standard bend radius G652D
Input cable type	External cable assembly module (ECAM)
Main cable diameter	6-18 mm
Main cable oval port count	1
Maximum number of fibers	24

BPEO Fibre Closure BPEO-S2-CDP



Design

Max number of trays	30
Maximum splice fiber capacity	720
Number of Cable Entries	8
Number of distribution/drop cables ports	6
Number of ports - cut	1
Number of splice trays	30
Sealing type	Rubber Gasket
Test valve	Included
Trays capacity	30

Ordering Information

Product Number	B2-CDP-0000-000-000-0000
Length	520 mm
Package contents	"ECAM S18, ECAM D27 (or 2x S18)"
Width	341 mm
Depth	149 mm
Units per delivery	1/1



Corning Optical Communications GmbH & Co. KG • Leipzig Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2023 Corning Optical Communications. All rights reserved.