

K7 Splice Cassette 1 Slot, Uni Zone-12

The CORNING logo is displayed in white, uppercase letters within a solid blue rectangular box.

Part Number:
FQ100068284

The type of splice technology used (fusion or mechanical) and whether planar light circuit (PLC) splitters are required will help determine which BPEO splice tray should be selected.

- Compact trays are 5 mm in height and occupy one slot in the fibre organiser.
- Standard trays are 10 mm in height and occupy two slots.
- All BPEO splice trays accept heat-shrink fusion splice protectors of 2.4 mm x 45 mm or 2.4 mm x 60 mm (after shrinkage). For example, Fibre Closure BPEO size 1 is equipped with a 12-slot fibre organiser. If using a 5 mm tray for 12 fusion splices, the total capacity of the closure will be 144 splices.

K7 Splice Cassette 1 Slot, Uni Zone-12

CORNING

Specifications

General Specifications

Brand	BPEO
Product type	K7 Tray / Kasette

Standards

Fibre Standards	G.652 / G.657
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

Design

Splice tray type	Splice Tray
Splice tray category	Standard bend radius G652D
Number of splice trays	1
Splice protectors type	Heat shrink, single fibre
Splice Tray Capacity Mass Fusion	0
Splice tray capacity single fibre	12
Number of splice protectors	12

Dimensions

Height	10 mm
--------	-------

Ordering Information

Product Number	FQ100068284
Package contents	20
Packaging method	Box
Module Capacity	0
Units per delivery	20/1

K7 Splice Cassette 1 Slot, Uni Zone-12

The CORNING logo is displayed in white, uppercase letters within a solid blue square.

Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2025 Corning Optical Communications. All rights reserved.