

RGH15

WORK POSITIONING COMFORT HARNESS RGH15

This work positioning safety harness is perfect for lengthy hands free tasks, due to its lumbar supporting work positioning belt. The belt makes up two of the four connection points of this harness, the other two being front and rear attachment points.

This comfortable harness is perfect for operatives who are required to work at height or in exposed areas for prolonged periods of time. The unique design allows the shoulder straps to follow the user's movement.

The addition of easy to use tail tidies means excess webbing won't hinder the user during work. If combined with a twin leg lanyard the safety harness can be used for tower climbing, scaffold work and general steel erecting.

- / Front, rear & side attachment points
- / Waist, leg & shoulder support pads
- / Work positioning D rings
- / Tool Loops
- / Tail Tidies

EN 361:2002

EN 358:2018

Web material:	45mm RIDGE Protect anti-bacterial polyester*
Max user weight:	140kg
Fittings:	High tensile steel alloy Aluminium lightweight D rings
Weight:	2.1kg



FRONT VIEW



* 14 times reduction in bacterial growth, according to ISO 20743:2013 contact with *K.pneumoniae*, commonly associated with healthcare infections such as *E.coli*



RGH15
FEATURES



BACK VIEW



Waist, leg & shoulder support pads



Front, rear, side & ventral attachment points



Adjustable fast fit buckles on leg and front chest straps



Double front waist adjustable



Rear waist adjuster for repositioning of side D rings



Work positioning D rings



Back & shoulder adjuster



Tail tides



Tool Loops

SIZE GUIDE

Correct sizing is essential to the safety and comfort of a safety harness. Use this table to help select the appropriate size and feel free to give us a call if you need any assistance.

Size	STANDARD	LARGE
A Chest	36 - 50" 91 - 127cm	46 - 58" 117 - 147cm
B Waist	30 - 44" 76 - 111cm	40 - 52" 102 - 132cm
C Hips	38 - 52" 96 - 132cm	48 - 60" 122 - 152cm

