

FRONT VIEW

RGM2

FRONT & REAR D SAFETY HARNESS

RGH2

This two point safety harness has both a rear and chest mounted front attachment point.

The two attachment points extend this harness's working capability. Meaning it can be used for fall protection and restraint situations in either vertical or horizontal planes. The ring connection between the chest and shoulder straps ensures no stress loading when force is applied to the front D ring. High contrast stitching makes inspection easier. The addition of a flexible rear D pad provides additional comfort. The inclusion of easy slide shoulder buckles increases the range of adjustment. The way the harness has been designed minimises the amount of rigid webbing edges. A variety of devices can be used with the harness, but check for suitability.

/ Front & rear attachment point

EN 361:2002

Web material: 45mm RIDGE Protect anti-bacterial polyester*

Max user weight: 140kg

Fittings: High tensile steel alloy

Weight: 1.1kg standard

1.3kg comfort







^{* 14} times reduction in bacterial growth, according to ISO 20743:2013 contact with K.pneumoniae, commonly associated with healthcare infections such as E.coli





RIDGEGEAR PRODUCT DATA SHEET



RGH2 FEATURES







Rip stitch indicators



Rear attachment point




Front attachment point

BACK VIEW

SIZE GUIDE

Correct sizing is essential to the safety and comfort of a safety harness. Use this table to help select the appropriate size and feel free to give us a call if you need any assistance.


Size	SMALL	STANDARD	LARGE	X-LARGE
A	36 - 42"	42 - 50"	50 - 54"	54 - 58"
Chest	91 - 107cm	107 - 127cm	127 - 137cm	137 - 147cm
B	30 - 36"	36 - 44"	44 - 48"	48 - 52"
Waist	76 - 91cm	91 - 111cm	111 - 122cm	122 - 132cm
C	38 - 44"	44 - 52"	52 - 56"	56 - 60"
Hips	97 - 112cm	112 - 132cm	132 - 142cm	142 - 152cm







Nelson Street, Leek, Staffordshire, ST13 6BB



sales@ridgegear.com



