

TELENCO® DS SUSPENSION CLAMPS FOR ROUND ADSS CABLES



The Telenco® DS suspension clamps are designed to provide a mobile suspension for 5 to 17mm aerial round ADSS cables. These clamps are to install on intermediate poles used for the roll-out of access networks where spans do not exceed 70m.

The Telenco® DS suspension clamps consist of a nylon body with an integrated suspension bail and a neoprene insert sleeve.

A bolt is used to lock the body and secure the cable installed into the neoprene insert.



PN	MODEL	Ø CABLE	MATERIAL			⚖️	PACKG
			BODY	SLEEVE	SCREWS		
09938	DS5	5 – 8mm	UV protected nylon	UV protected neoprene	Steel	0.13 kg	30 units
09215	DS8	8 – 12mm					
09173	DS12	12 – 15mm					
09556	DS15	15 – 18mm					

FEATURES & BENEFITS

- Only four sizes covering the ADSS cable range Ø 5 to 17mm
- Installation runs in a few seconds with a 13mm standard 6-point spanner
- Vertical tensile strength > 2300N
- The clamp's bail provides additional protection to the cable against wind induced vibrations

INSTALLATION

Telenco® DS suspension clamps are to be installed on cross-arms or suspension brackets.

